

People is our Base.....



Customer Satisfaction
is our Goal



Specification of

LADDAR LIFT

- Loading Capacity - 300 Kgs
- Working Height - 54 (Feet)
- Prime Mover - 6 to 8 HP Air cooled Diesel Engine



SLS ENGINEERING INDUSTRY

Manufacturers of : Concrete Mixer Machines and Construction Equipments

7/52A, Avinashi Road, RG Pudur Pirivu, Chinnampalayam, Coimbatore - 641 062.

Ph : 2629940, Cell : 94430 52834, E-mail: slsengine@yahoo.com



Specification of

WEIGH BATCHER SPECIFICATION

Type : Pan type without Spring and Dial
 Capacity : 420 Kgs
 Weight : 500 Kgs (Approx)

- Considerable Labour Charge
- Portable
- Wire Mesh Changeable
- Power : 0.5 Single Phase Motor / Manual
- Siever Size : 36", 48", 72", Length X 26 ½ Dia



❖ **VIBRATER EARTH RAMMER**



❖ **Hand Mixer (1.5 HP)**



Specification of

CONCRETE VIBRATOR

- ❖ 12 ft 20 Long flexible shaft
- ❖ 25 mm x 375 mm
- ❖ 40 mm x 450 mm
- ❖ 60 mm dia Vibrating Needle



❖ **3 cft Double Wheel barrow (Scooter Tyre)**



❖ **Tar Work Heavy Type Wheel barrow & Stove**

Mobile Hoist With Concrete Mixer Machine		
Hoist Capacity	½ Ton	1 Ton
Speed Metre / Min	25	25
Prime Mover HP	10	12
Tower 'I' Section	50x50x6 / 65x65x6	50x50x6 / 65x65x6
Rop dia mm	12	14
Mixer machine cft	7/5	10/7 Hydraulic Hopper
Pipe mm 'c' class	42,48	42,48